

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023



Page 1 of 12

Print date: 01/01/2023

SECTION 1: IDENTIFICATION OF THE MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: StrataShield FC Sealer Coat - Part A

1.2 Relevant identified uses of the mixture and uses advised against.

Coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **Strata Waterproofing**

Address: Unit 3, Kilwee Business Park, Upper Dunmurry Lane Dunmurry,
Belfast, BT17 0HD
United Kingdom

Telephone: 028 9030 2924

E-mail: Email: info@stratawaterproofing.com

Web: www.stratawaterproofing.com

1.4 Emergency telephone number: 028 9030 2924 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed.

Aquatic Chronic 3 : Harmful to aquatic life with long lasting effects.

Eye Dam. 1 : Causes serious eye damage.

Flam. Liq. 3 : Flammable liquid and vapour.

Skin Corr. 1B : Causes severe skin burns and eye damage.

Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Danger

H statements:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.

P statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly with soap and water after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023



Page 2 of 12

Print date: 01/01/2023

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P370+P378 In case of fire: Use dry powder or dry sand to extinguish.

Contains:
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate
N,N'-bis(2-propyl)polyoxypropylenediamine

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 607-521-00-8 CAS No: 136210-30-5 EC No: 429-270-1 Registration No: 01-0000017556-64-XXXX	tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate	25 - 50 %	Aquatic Chronic 3, H412 - Skin Sens. 1, H317	-
CAS No: 81455-53-0	N,N'-bis(2-propyl)polyoxypropylenediamine	25 - 50 %	Acute Tox. 4, H302 - Aquatic Chronic 3, H412 - Eye Dam. 1, H318 - Skin Corr. 1B, H314	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene (Mixture of isomers)	10 - 25 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	1 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-
Index No: 607-195-00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01-2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	0 - 2.5 %	Flam. Liq. 3, H226	-

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023



Page 3 of 12

Print date: 01/01/2023

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.

Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Corrosive Product, contact with eyes or skin can cause burns; ingestion or inhalation can cause internal damage, if this occurs immediate medical assistance is required.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023



Page 4 of 12

Print date: 01/01/2023

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Pick up the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomite, etc.). Pour the product and the absorbent in an appropriate container. The contaminated area should be immediately cleaned with an appropriate decontaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5b	FLAMMABLE LIQUIDS	50	200

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
xylene (Mixture of isomers)	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
		United Kingdom [2]	Eight hours	50	220
			Short term	100	441
ethylbenzene	100-41-4	European Union [1]	Eight hours	100 (skin)	442 (skin)
			Short term	200 (skin)	884 (skin)
		United Kingdom [2]	Eight hours	100	441
			Short term	125	552

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)



StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023

Page 5 of 12

Print date: 01/01/2023

2-methoxy-1-methylethyl acetate	108-65-6	European Union [1]	Eight hours	50 (skin)	275 (skin)
			Short term	100 (skin)	550 (skin)
		United Kingdom [2]	Eight hours	50	274
			Short term	100	548

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

[2] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
tetraethyl N,N'-(methylenedicyclohexane-4,1-diyl)bis--aspartate CAS No: 136210-30-5 EC No: 429-270-1	DNEL (Workers)	Inhalation, Long-term, Systemic effects	84 (mg/m ³)
xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m ³)
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	77 (mg/m ³)
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	DNEL (Workers)	Inhalation, Long-term, Systemic effects	275 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	33 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	153,5 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	54,8 (mg/kg bw/day)
	DNEL (General population)	Oral, Long-term, Systemic effects	1,67 (mg/kg bw/day)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	aqua (freshwater)	0,635 (mg/L)
	aqua (marine water)	0,0635 (mg/L)
	aqua (intermittent releases)	6,35 (mg/L)
	PNEC STP	100 (mg/L)
	sediment (freshwater)	3,29 (mg/kg sediment dw)
	sediment (marine water)	0,329 (mg/kg sediment dw)
	soil	0,29 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Coating
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.



-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)





StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023

Page 6 of 12

Print date: 01/01/2023

Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.		
CEN standards:	EN 136, EN 140, EN 405		
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor. Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Observations:	the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Non-disposable protective gloves against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals for which the glove has been tested.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	A schedule for the periodical replacement of gloves should be established in order to guarantee their replacement before pollutants permeate them. The use of contaminated gloves could be more dangerous than not using gloves, since the pollutant can gradually accumulate in the glove's material.		
Observations:	They are to be replaced whenever tears, cracks or deformations are observed or when exterior dirt could reduce their strength.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.): > 480	
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
PPE:	Chemical protective clothing		
Characteristics:	«CE» marking, category III. Clothing should fit properly. The level of protection must be set according to a test parameter called BT (Breakthrough Time), which indicates how long it takes for the chemical to pass through the material.		
CEN standards:	EN 464, EN 340, EN 943-1, EN 943-2, EN ISO 6529, EN ISO 6530, EN 13034		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing's design should facilitate correct positioning, staying in place without moving for the period of use expected, bearing in mind environmental factors as well as any movement or position the user might adopt while carrying out the activity.		
PPE:	Anti-static safety footwear against chemicals.		
Characteristics:	«CE» marking, category III. Check the list of chemicals against which the footwear is resistant.		
CEN standards:	EN ISO 13287, EN 13832-1, EN 13832-2, EN 13832-3, EN ISO 20344, EN ISO 20345		
Maintenance:	For correct maintenance of this kind of safety footwear, it is necessary to observe the instructions specified by the manufacturer. The footwear should be replaced as soon as any sign of damage is observed.		
Observations:	The footwear should be cleaned regularly and dried when damp, although it should not be placed too close to a source of heat in order to avoid any sharp changes in temperature.		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Liquid with characteristic odour and colour

Colour: colourless or pigmented

Odour: solvent

Odour threshold: N.A./N.A.

pH: not applicable

Melting point: not determined °C

Boiling Point: 209 °C

Flash point: 38 °C

Evaporation rate: not determined

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A



Version: 1
Revision date: 01/01/2023

Page 7 of 12
Print date: 01/01/2023

Inflammability (solid, gas): flammable
Lower Explosive Limit: not determined
Upper Explosive Limit: N.A./N.A.
Vapour pressure: not determined
Vapour density: not determined
Relative density: 0,90 g/cm³
Solubility: organic solvents
Liposolubility: soluble
Hydrosolubility: insoluble
Partition coefficient (n-octanol/water): not determined
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: <100 mPa.s at 20°C
Explosive properties: not determined
Oxidizing properties: not determined

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Pour point: not determined
Blink: not determined
Kinematic viscosity: not determined
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid the following conditions:

- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.

Avoid the following materials:

- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.

In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on toxicological effects.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A



Version: 1
Revision date: 01/01/2023

Page 8 of 12
Print date: 01/01/2023

xylene (Mixture of isomers) CAS No: 1330-20-7 EC No: 215-535-7	Oral	LD50 Rata/Rat 4300 mg/kg bw [1] [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
	Dermal	LD50 Rabbit/Cone jo > 1700 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
	Inhalation	LC50 Rat/Rata 21,7 mg/l/4 h [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974

a) acute toxicity;
Product classified:
Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):
Mixtures:
ATE (Dermal) = 4.524 mg/kg
ATE (Oral) = 1.730 mg/kg

b) skin corrosion/irritation;
Product classified:
Skin Corrosive, Category 1B: Causes severe skin burns and eye damage.

c) serious eye damage/irritation;
Product classified:
Serious eye damage, Category 1: Causes serious eye damage.

d) respiratory or skin sensitisation;
Product classified:
Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Not conclusive data for classification.

i) STOT-repeated exposure;
Based on available data, the classification criteria are not met.

j) aspiration hazard;
Based on available data, the classification criteria are not met.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
xylene (Mixture of isomers)	Fish	LC50	Fish/Pez	15,7 mg/l (96 h) [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A



Version: 1
Revision date: 01/01/2023

Page 9 of 12
Print date: 01/01/2023

CAS No: 1330-20-7 EC No: 215-535-7		[1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212
	Aquatic invertebrates	LC50 Crustacean 8,5 mg/l (48 h) [1] [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p
	Aquatic plants	

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A



Version: 1
Revision date: 01/01/2023

Page 10 of 12
Print date: 01/01/2023

14.1 UN number.

UN No: UN1866

14.2 UN proper shipping name.

Description:

ADR: UN 1866, RESIN SOLUTION, 3, PG III, (D/E)

IMDG: UN 1866, RESIN SOLUTION, 3, PG III (38°C)

ICAO: UN 1866, RESIN SOLUTION, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No

14.6 Special precautions for user.

Labels: 3



Hazard number: 30

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-E

Proceed in accordance with point 6.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): Two-pack reactive performance coatings for specific end use such as floors, solvent-borne

Phase I* (from 01/01/2007): 550 g/l

Phase II* (from 01/01/2010): 500 g/l

(*) g/l ready to use

VOC content (p/p): 31 %

VOC content: 307 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): P5b

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A

Version: 1

Revision date: 01/01/2023



Page 11 of 12

Print date: 01/01/2023

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H373	May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganosdeaudición)
H412	Harmful to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 [Dermal] : Acute toxicity (Dermal), Category 4
Acute Tox. 4 [Inhalation] : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 [Oral] : Acute toxicity (Oral), Category 4
Aquatic Chronic 3 : Chronic effect to the aquatic environment, Category 3
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.
PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

StrataShield FC Sealer Coat - Part A



Version: 1
Revision date: 01/01/2023

Page 12 of 12
Print date: 01/01/2023

Regulation (EU) 2015/830.
Regulation (EC) No 1907/2006.
Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.